



U 124597A

United States Patent [19]

[11] Patent Number: 6,124,597

Shehada et al.

[45] Date of Patent: Sep. 26, 2000

[54] **METHOD AND DEVICES FOR LASER
INDUCED FLUORESCENCE ATTENUATION
SPECTROSCOPY**

5,760,406 6/1998 Powers 250/461.2

FOREIGN PATENT DOCUMENTS

0 703 445 A2 9/1995 European Pat. Off. .

WO 89/12223 6/1989 WIPO .

WO 97/08538 8/1996 WIPO .

Primary Examiner—Constantine Hannaher

Assistant Examiner—Andrew Israel

Attorney, Agent, or Firm—Pretty, Schroeder & Poplawski

[75] Inventors: **Ramez E. N. Shehada**, Los Angeles;
Vasilis Z. Marmarelis, Irvine; **Warren
S. Grundfest**, Los Angeles, all of Calif.

[73] Assignee: **Cedars-Sinai Medical Center**, Los
Angeles, Calif.

[21] Appl. No.: **08/889,017**

[22] Filed: **Jul. 7, 1997**

[51] Int. Cl.⁷ **G01N 21/64**

[52] U.S. Cl. **250/461.2; 250/458.1;
600/321; 600/320; 600/323; 356/342**

[58] Field of Search **250/461.2, 458.1;
600/321, 320, 323; 356/342**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,641,650 2/1987 Mok .
4,675,529 6/1987 Kushida .
4,707,131 11/1987 Schiek .
4,753,530 6/1988 Knight et al. .
4,786,813 11/1988 Svanberg et al. .
4,945,245 7/1990 Levin .
4,957,114 9/1990 Zeng et al. .
5,122,974 6/1992 Chance .
5,341,805 8/1994 Stavridi et al. .
5,452,723 9/1995 Wu et al. .
5,456,252 10/1995 Vari et al. .
5,495,850 3/1996 Zuckerman .
5,507,287 4/1996 Palcic et al. .
5,635,402 6/1997 Alfano 436/63

[57] **ABSTRACT**

The Laser Induced Fluorescence Attenuation Spectroscopy (LIFAS) method and apparatus preferably include a source adapted to emit radiation that is directed at a sample volume in a sample to produce return light from the sample, such return light including modulated return light resulting from modulation by the sample, a first sensor, displaced by a first distance from the sample volume for monitoring the return light and generating a first signal indicative of the intensity of return light, a second sensor, displaced by a second distance from the sample volume, for monitoring the return light and generating a second signal indicative of the intensity of return light, and a processor associated with the first sensor and the second sensor and adapted to process the first and second signals so as to determine the modulation of the sample. The methods and devices of the inventions are particularly well-suited for determining the wavelength-dependent attenuation of a sample and using the attenuation to restore the intrinsic laser induced fluorescence of the sample. In turn, the attenuation and intrinsic laser induced fluorescence can be used to determine a characteristic of interest, such as the ischemic or hypoxic condition of biological tissue.

54 Claims, 17 Drawing Sheets